

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number
WO 2004/094960 A3

(51) International Patent Classification⁷: **G01F 1/66.**
G01N 29/02

(21) International Application Number:
PCT/JP2004/005590

(22) International Filing Date: 20 April 2004 (20.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-115333 21 April 2003 (21.04.2003) JP
2003-168911 13 June 2003 (13.06.2003) JP
2003-271779 8 July 2003 (08.07.2003) JP

(71) Applicant (for all designated States except US): **TEI-
JIN PHARMA LIMITED** [JP/JP]; 1-1, Uchisaiwaicho
2-chome, Chiyoda-ku, Tokyo 1008585 (JP).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **FUJIMOTO, Naoto-
shi** [JP/JP]; c/o Teijin Pharma Limited, Tokyo Research
Center, 3-2, Asahigaoka 4-chome, Hino-shi, Tokyo
1910065 (JP).

(74) Agents: **AOKI, Atsushi et al.; A. AOKI, ISHIDA & AS-
SOCIATES**, Toranomon 37 Mori Bldg., 5-1, Toranomon
3-chome, Minato-ku, Tokyo 1058423 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: **ULTRASONIC APPARATUS AND METHOD FOR MEASURING THE CONCENTRATION AND FLOW RATE OF
GAS**



(57) Abstract: **ABSTRACT** An ultrasonic apparatus measures the concentration and flow rate of a sample gas by calculating a possible propagation time range on the basis of the gas temperature, determining whether or not the phases at which two first trigger signals, respectively generated on the basis of forward and backward waveforms of the ultrasonic waves, coincide with each other, processing the zero-cross signals so that the phases coincide with each other, obtaining reference zero-cross time instant by calculating mean value of the forward and backward zero-cross time instants, obtaining an ultrasonic reception point by subtracting an integral multiple of the cycle of the ultrasonic waves so that the results of the subtraction falls into a possible propagation time range and estimating the ultrasonic propagation time on the basis of the ultrasonic reception point.

WO 2004/094960 A3



(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:

16 June 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

13/pets
- 1 -

10/550687

DESCRIPTION

JC20 Rec'd PCT/PTO 26 SEP 2005

ULTRASONIC APPARATUS AND METHOD FOR MEASURING THE
CONCENTRATION AND FLOW RATE OF GAS

5 Technical Field

The invention relates to ultrasonic apparatus and method for measuring the concentration of oxygen gas in a sample gas and flow rate of the sample gas, which is supplied from an oxygen concentrator used for a medical purpose.

Background Art

It is well known that the propagation velocity of ultrasonic waves through a sample gas is presented by a function of the concentration and the temperature of the sample gas. The velocity C(m/sec) of ultrasonic waves propagating through a stationary gas is presented by flowing equation (1) with mean molecular weight M and the temperature T(K).

20
$$C = (\kappa RT / M)^{1/2} \dots (1)$$

Where:

κ : ratio of molecular specific heat at constant volume and molecular specific heat at constant pressure

R: gas constant

25 Therefore, measuring the velocity of ultrasonic waves C(m/sec) propagating through a sample gas and the temperature T(K) of the sample gas will provide the mean molecular weight M of the sample gas through a calculation. For example, the mean molecular weight M of a sample gas containing an oxygen-nitrogen gas mixture of a mixture ratio P:(1-P) ($0 \leq P \leq 1$) will be calculated by following equation (2).

$$M = M_{O_2}P + M_{N_2}(1-P) \dots (2)$$

Where:

35 M_{O_2} : Molecular Weight of oxygen gas

M_{N_2} : Molecular Weight of nitrogen gas

Therefore, the oxygen concentration P will be obtained through a calculation on the basis of the measurement of mean molecular weight M. When the sample gas is an oxygen-nitrogen mixture, $\kappa=1.4$ is reasonable over a wide range of the oxygen-nitrogen mixture ratio.

When the velocity of ultrasonic waves propagating through a sample gas is $C(\text{m/sec})$ and the flow velocity of the sample gas is $V(\text{m/sec})$, the velocity of ultrasonic waves $C_1(\text{m/sec})$ propagating in the forward direction relative to the sample gas flow is $C_1=C+V$, and the velocity of ultrasonic waves $C_2(\text{m/sec})$ propagating in the backward direction relative to the sample gas flow is $C_2=C-V$. Therefore, the velocity of the sample gas flow $V(\text{m/sec})$ is calculated by following equation (3).

$$V=(C_1-C_2)/2 \dots (3)$$

The flow rate (m^3/sec) of the sample gas will be obtained by multiplying the velocity of the sample gas flow by the sectional area (m^2) of the conduit through which the sample gas flows.

Methods and apparatuses for measuring the concentration of a certain gas or the flow velocity of a sample gas, by using the above principle, on the basis of the propagation velocity or the propagation time of ultrasonic waves through the sample gas have been developed. For example, Japanese Unexamined Patent Publication (Kokai) No. 6-213877 describes an apparatus for measuring the concentration and the flow rate of a sample gas by measuring the propagation time of ultrasonic waves propagating between two ultrasonic transducers opposingly disposed in a conduit through which the sample gas flows. Further, Japanese Unexamined Patent Publications (Kokai) No. 7-209265 and No. 8-233718 describe an apparatus for measuring the concentration of a certain gas contained in a sample gas by measuring the propagation velocity or propagation time of ultrasonic waves propagating through a volume with a reflecting type

apparatus including an ultrasonic transducer and an opposingly disposed reflector.

5 In such a method and an apparatus for measuring the concentration and the flow rate by using the propagation velocity of the ultrasonic waves, it is necessary to accurately measure the propagation time of the ultrasonic waves. However, the signal generated on the basis of the received ultrasonic waves always includes noise component, which makes difficult to determine the moment
10 when ultrasonic waves are received by the ultrasonic transducer. Therefore, the propagation time of ultrasonic waves is indirectly estimated through a complex signal processing procedure or a complex hardware. For example, Japanese Unexamined Patent
15 Publication (Kokai) No. 9-318644 describes a method for measuring a propagation time of ultrasonic waves in which the waveform of the received ultrasonic waves is integrated. After the results of the integration of the waveform reach a predetermined value, the first zero-cross
20 time instant is determined as the propagation time of the ultrasonic waves for the measurement of the flow rate. According to the method, the timing of the generation of the zero-cross signal is not fluctuated even if the amplitude of the received waves is fluctuated to some
25 extent. Therefore, the obtained zero-cross time instant is relatively close to the moment when the ultrasonic waves actually reach. However, the obtained zero-cross time instant is not real propagation time of the ultrasonic waves. In particular, when the concentration
30 is measured, the measurement error is strongly affected by the difference between the real propagation time and the zero-cross time instant.

Further, Japanese Unexamined Patent Publication (Kokai) No. 60-138422 describes a flow rate measuring
35 device in which an envelope curve is calculated on the basis of the waveform of the received ultrasonic waves. The rise time of the envelope curve is calculated by an

approximate equation to estimate the ultrasonic propagation time. However, a hardware is necessary to sample the received ultrasonic waves and a complex signal processing is necessary to calculate the envelope curve based on the sampled waveform. Therefore, according to the invention of JPP '422, it is difficult to provide a compact device with low cost.

Disclosure of the Invention

The object of the invention is to provide an ultrasonic apparatus and method for measuring concentration and flow rate of gas, which allow to accurately measure the concentration and flow rate of a sample gas without a complex signal processing and an additional hardware.

According to the present invention, there is provided an ultrasonic apparatus for measuring the concentration and flow rate of a sample gas, comprising:

a conduit for flowing the sample gas;
a first ultrasonic transmission-reception device mounted to the inside of the conduit;

a second ultrasonic transmission-reception device mounted to the inside of the conduit to face the first ultrasonic transmission-reception device;

a transmission-reception switch for switching the operation mode of the first and second ultrasonic transmission-reception devices between a transmission mode for transmitting ultrasonic waves and a reception mode for receiving ultrasonic waves;

a temperature sensor, disposed in the conduit, for measuring the temperature of the sample gas flowing through the conduit;

the first ultrasonic transmission-reception device generating forward ultrasonic waves relative to the flow direction of the sample gas when the device is in the transmission mode and generating backward waveform when the device is in the reception mode on the basis of the

received ultrasonic waves generated by the second ultrasonic transmission-reception device;

5 the second ultrasonic transmission-reception device generating backward ultrasonic waves relative to the flow direction of the sample gas when the device is in the transmission mode and generating forward waveform when the device is in the reception mode on the basis of the received ultrasonic waves generated by the first ultrasonic transmission-reception device;

10 means for generating trigger signals when the forward and backward waveforms pass over a predetermined level;

means for generating forward and backward zero-cross signals when the forward and backward waveforms pass over a zero level;

15 propagation time calculation means, coupled to the temperature sensor, the trigger signal generating means and the zero-cross signal generating means, for (1) calculating a possible propagation time range on the basis of the gas temperature detected by the temperature sensor, (2) determining whether or not the phases at which two first trigger signals, respectively generated on the basis of the forward and backward waveforms, coincide with each other, (3) processing the zero-cross signals so that the phases coincide with each other if they do not coincide with each other, (4) obtaining reference zero-cross time instant by calculating mean value of the forward and backward zero-cross time instants, (5) obtaining an ultrasonic reception point by subtracting an integral multiple of the cycle of the ultrasonic waves so that the results of the subtraction falls into the possible propagation time range and (6) estimating the ultrasonic propagation time on the basis of the ultrasonic reception point.

35 Further, according to another feature of the invention, there is provided a method of measuring the concentration of sample gas flowing through a conduit,

comprising the steps of:

generating forward ultrasonic waves relative to the flow direction of the sample gas;

5 generating backward ultrasonic waves relative to the flow direction of the sample gas;

measuring the temperature of the sample gas flowing through the conduit;

generating trigger signals when the forward and backward waveforms pass over a predetermined level;

10 generating forward and backward zero-cross signals when the forward and backward waveforms pass over a zero level;

calculating a possible propagation time range on the basis of the gas temperature detected by the temperature sensor;

15 determining whether or not the phases at which two first trigger signals, respectively generated on the basis of the forward and backward waveforms, coincide with each other;

20 processing the zero-cross signals so that the phases coincide with each other if they do not coincide with each other;

obtaining reference zero-cross time instant by calculating mean value of the forward and backward zero-cross time instants;

25 obtaining an ultrasonic reception point by subtracting an integral multiple of the cycle of the ultrasonic waves so that the results of the subtraction falls into the possible propagation time range; and

30 estimating the ultrasonic propagation time on the basis of the ultrasonic reception point.

Further, according to another feature of the invention, there is provided an oxygen concentration system for generating an oxygen enriched gas, comprising
35 an oxygen concentration apparatus for generating an oxygen enriched gas by adsorbing nitrogen to remove the nitrogen from the air; and

an ultrasonic apparatus for measuring the concentration of the oxygen in the oxygen enriched gas and flow rate of the oxygen enriched gas, the ultrasonic apparatus comprising:

5 a conduit for receiving and flowing the oxygen enriched gas;

 a first ultrasonic transmission-reception device mounted to the inside of the conduit;

10 a second ultrasonic transmission-reception device mounted to the inside of the conduit to face the first ultrasonic transmission-reception device;

15 a transmission-reception switch for switching the operation mode of the first and second ultrasonic transmission-reception devices between a transmission mode for transmitting ultrasonic waves and a reception mode for receiving ultrasonic waves;

 a temperature sensor, disposed in the conduit, for measuring the temperature of the oxygen enriched gas flowing through the conduit;

20 the first ultrasonic transmission-reception device generating forward ultrasonic waves relative to the flow direction of the oxygen enriched gas when the device is in the transmission mode and generating backward waveform when the device is in the reception mode on the basis of
25 the received ultrasonic waves generated by the second ultrasonic transmission-reception device;

30 the second ultrasonic transmission-reception device generating backward ultrasonic waves relative to the flow direction of the oxygen enriched gas when the device is in the transmission mode and generating forward waveform when the device is in the reception mode on the basis of
 the received ultrasonic waves generated by the first ultrasonic transmission-reception device;

35 means for generating trigger signals when the forward and backward waveforms pass over a predetermined level;

 means for generating forward and backward zero-cross

signals when the forward and backward waveforms pass over a zero level;

5 propagation time calculation means, coupled to the temperature sensor, the trigger signal generating means and the zero-cross signal generating means, for (1) calculating a possible propagation time range on the basis of the gas temperature detected by the temperature sensor, (2) determining whether or not the phases at which two first trigger signals, respectively generated
10 on the basis of the forward and backward waveforms, coincide with each other, (3) processing the zero-cross signals so that the phases coincide with each other if they do not coincide with each other, (4) obtaining reference zero-cross time instant by calculating mean
15 value of the forward and backward zero-cross time instants, (5) obtaining an ultrasonic reception point by subtracting an integral multiple of the cycle of the ultrasonic waves so that the results of the subtraction falls into the possible propagation time range and (6)
20 estimating the ultrasonic propagation time on the basis of the ultrasonic reception point.

Further, according to another feature of the invention, there is provided an oxygen concentration system for generating an oxygen enriched gas, comprising:

25 an oxygen concentration apparatus for generating an oxygen enriched gas by adsorbing nitrogen to remove the nitrogen from the air; and

an ultrasonic apparatus for measuring the concentration of the oxygen in the oxygen enriched gas
30 and flow rate of the oxygen enriched gas, the ultrasonic apparatus comprising:

a conduit for flowing an objective gas, the concentration of which is to be measured;

35 a first ultrasonic transmission-reception device mounted to the inside of the conduit;

a second ultrasonic transmission-reception device mounted to the inside of the conduit to face the first

ultrasonic transmission-reception device;

the conduit includes a straight portion and perpendicular portions perpendicularly connected to the ends of the straight portion;

5 the first and second ultrasonic transmission-reception devices are disposed in the perpendicular portions to face the ends of the straight portion; and

the distance between the first and second ultrasonic transmission-reception devices and the respective ends of the straight portion of the conduit satisfying the following relation.

$$0 < D < f - r^2 / C$$

where:

D: the distance (m) between the first and second
15 ultrasonic transmission-reception devices and the respective ends of the straight portion

f: frequency of the ultrasonic waves in the sample gas (Hz)

r: inner radius of the conduit (m)

20 C: velocity of the ultrasonic waves (m/sec)

Brief Description of the Drawings

Figure 1 is a schematic diagram of an oxygen concentration apparatus according to the invention;

25 Figure 2 is a schematic diagram of an ultrasonic apparatus of the invention;

Figure 3A is a waveform based on the received ultrasonic waves;

30 Figure 3B is an enlarged illustration of a portion of the waveform shown in Figure 3A;

Figure 4 is an illustration showing the ultrasonic waveform with the trigger signals and the zero-cross signals;

35 Figure 5 is a graph showing the relation between the velocity of the ultrasonic waves and the temperature;

Figure 6 is an illustration showing forward and backward ultrasonic waveforms in case that the phases, at

which the trigger signals are generated, coincide with each other;

5 Figure 7 is an illustration similar to that of Figure 6 in case that the phases do not coincide with each other;

 Figure 8 is an illustration similar to that of Figure 6 in case that the phases do not coincide with each other;

10 Figure 9 is an explanatory illustration for explaining the way for obtaining the zero-cross time instant with an assumption that the sample gas is in stationary state;

15 Figure 10 is an explanatory illustration for explaining the way for obtaining the ultrasonic reception point;

 Figure 11 is a section of the ultrasonic apparatus according to another embodiment of the invention;

20 Figure 12 is an explanatory illustration for explaining the sound field formed at the front of an ultrasonic transducer;

 Figures 13 shows experimental results of ultrasonic waveforms which were obtained by an apparatus of Figure 11;

25 Figures 14 shows experimental results of ultrasonic waveforms which were obtained by an apparatus of Figure 11; and

 Figures 15 shows experimental results of ultrasonic waveforms which were obtained by an apparatus of Figure 11.

30

Best Mode for Carrying out the Invention

35 A preferred embodiment of the present invention will be described below. In the embodiment described below, a sample gas is composed of a mixture of oxygen and nitrogen. However, the measurable sample gas is not limited to a sample gas of oxygen and nitrogen and the present invention can be supplied to a mixture including

another gas.

Figure 1 shows a schematic diagram of an oxygen concentration system having an ultrasonic gas concentration and flow rate measuring apparatus according to a preferred embodiment of the present invention.

The apparatus 100 includes an oxygen concentration apparatus 102 which produces an oxygen enriched gas by removing nitrogen from the air supplied by a compressor 104 from the outside of the system through a filter 106. The oxygen enriched gas produced by the oxygen concentration apparatus 102 is supplied to an ultrasonic apparatus 200 of the present invention through a flow rate setting device 108, such as a pressure reduction valve. The produced oxygen enriched gas is then supplied to a user or a patient through a production filter 110.

The oxygen concentration apparatus includes a plurality of columns (not shown) for accommodating nitrogen adsorbent such as a zeolite, a piping system (not shown) including conduits for directing the compressed air from the compressor 104 to each of the plurality of columns and for directing the produced oxygen enriched gas from the columns to the flow rate setting device 108 and valves (not shown) disposed in the piping system for selectively opening and closing the conduits so that the adsorbent contained in one of the columns adsorbs nitrogen to produce the oxygen enriched gas and the adsorbent contained in the other columns release the adsorbed nitrogen for the regeneration of the adsorbent.

With reference to Figure 2, the ultrasonic apparatus 200 of the present invention for measuring the concentration and the flow rate of a sample gas will be described below.

The gas concentration and flow rate measuring apparatus 200 includes a conduit 202 for flowing a sample gas or the oxygen enriched gas produced by the oxygen concentration apparatus 102. The conduit 202 has a

straight portion 208 and perpendicular portions 204 and 206 connected to the ends of the straight portion. The straight portion 208 comprises a conduit member having a circular section, the diameter of which does not changes along the longitudinal axis. A first ultrasonic transducer 218, providing a first ultrasonic transmission-reception device, is fixedly provided at an end of the inside of the straight portion, and a second ultrasonic transducer 222, providing a second ultrasonic transmission-reception device, is fixedly mounted to the other end of the inside of the straight portion 208 to face the first ultrasonic transducer 218. In this embodiment, the distance between the first and second ultrasonic transducers 218 and 222 is referred to a propagation length L_s .

The perpendicular portion 204, disposed at the upstream side relative to the flow direction of the gas through the conduit 202, has an inlet port 204a. The oxygen concentration apparatus 102 is connected to the inlet port 204a as a sample gas source 212 through a supply conduit 210.

The perpendicular portion 206, disposed at the downstream side relative to the flow direction of the gas through the conduit 202, has an outlet port 206a to which the production filter 110 is connected.

A transmission-reception switch 224 is connected to the first and second ultrasonic transducers 218 and 222. The transmission-reception switch 224 independently switches the operation mode of the first and second ultrasonic transducers 218 and 222 between a transmission mode in which the first and second ultrasonic transducers 218 and 222 transmit ultrasonic waves and a reception mode in which the first and second ultrasonic transducers 218 and 222 receive the ultrasonic waves. The transmission-reception switch 224 is connected to a microcomputer 226 so that the switching operation of transmission-reception switch 224 is controlled by the

microcomputer 226.

Temperature sensors 216 and 220, for measuring the temperature of the gas flowing through the conduit 202, are disposed preferably in the perpendicular portions 204 and 206 so that they do not disturb the flow in the straight portion 208. The temperature sensors 216 and 220 are connected to the microcomputer 226. In this connection, if the changes in the temperature of the sample gas is small, only one of the temperature sensors 216 or 220 may be disposed.

A driver 228 for driving the first and second ultrasonic transducers 218 and 222, a zero-cross detection circuit 230 for detecting zero-cross time instants of the signals from the first and second ultrasonic transducers 218 and 222, a display unit 234 for indicating, for example, the operating condition of the device 200 and the measurement results and memory 232 including a nonvolatile memory device or a disc device for storing the operation system for the microcomputer 226 and various parameters are connected to the microcomputer 226.

The operation of the ultrasonic concentration and flow rate measuring apparatus 200 of the present embodiment will be described below.

A sample gas, for example an oxygen-nitrogen gas mixture the mixture ratio of which is $P:(1-P)$ ($0 \leq P \leq 1$), is supplied to the conduit 202. At that time, the temperatures of the sample gas are measured by the temperature sensors 216 and 220 and the mean value thereof is stored in the memory 232 as a reference temperature $T_0(K)$. According to the embodiment, the working temperature range of the system 100 is preferably selected, for example 5-35 Celsius degrees.

During the supply of the sample gas, pulses for generating the ultrasonic waves are transmitted to the driver 228 from the microcomputer 226. A pulse voltage is supplied to the first ultrasonic transducer 218 from

the driver 228 through the transmission-reception switch 224. The first ultrasonic transducer 218 generates ultrasonic waves corresponding to the pulse voltage. The ultrasonic waves generated by the first ultrasonic transducer 218 propagate through the sample gas flowing through the straight portion 208 of the conduit 202 and are received by the second ultrasonic transducer 222. The second ultrasonic transducer 222 generates an electric signal corresponding to the received ultrasonic waves to the microcomputer 226 through the transmission-reception switch 224 and the zero-cross detection circuit 230. The microcomputer 226 calculates the forward propagation time t_{s1} (sec) on the basis of the time when the transmitted pulses are generated to the driver 228 and the time when the electric signal is received from the second ultrasonic transducer 222.

Then, the transmission-reception switch 224 switches the operation mode of the first ultrasonic transducer 218 from the transmission mode to the reception mode right after the electric signal from the second ultrasonic transducer 222 is received and also switches the operation mode of the second ultrasonic transducer 222 from the reception mode to the transmission mode. Thereafter, pulses for generating the ultrasonic waves are transmitted to the driver 228 from the microcomputer 226. A pulse voltage is supplied to the second ultrasonic transducer 222 from the driver 228 through the transmission-reception switch 224. The second ultrasonic transducer 222 generates ultrasonic waves corresponding to the pulse voltage. The ultrasonic waves are received by the first ultrasonic transducer 218. The first ultrasonic transducer 218 generates an electric signal corresponding to the received ultrasonic waves to the microcomputer 226 through the transmission-reception switch 224 and the zero-cross detection circuit 230. The microcomputer 226 calculates the backward propagation time t_{s2} (sec) on the basis of the time when the

transmitted pulses are generated to the driver 228 and the time when the electric signal is received from the first ultrasonic transducer 218.

5 By obtaining the mean value of t_{s1} and t_{s2} , the affection of the flow of the sample gas in the conduit 202 can be removed. The ultrasonic propagation time t_s in the stationary sample gas is defined by following equation (4).

$$t_s = (t_{s1} + t_{s2}) / 2 \dots (4)$$

10 The microcomputer 226 then calculates the ultrasonic propagation velocity C_s (m/sec) through the stationary sample gas by flowing equation (5).

$$C_s = L_s / t_s \dots (5)$$

15 The concentration of oxygen P_s is obtained by following equation (6) on the basis of equations (1) and (2).

$$P_s = (\kappa R T_s / C_s^2 - M_{N_2}) / (M_{O_2} - M_{N_2}) \dots (6)$$

20 Further, the concentration of oxygen in the sample can be obtained as a ratio of the ultrasonic propagation velocity in the sample gas and the ultrasonic propagation velocities in 100% of oxygen gas and 100% of nitrogen gas. That is, the ultrasonic propagation velocity C_{O_2} (m/sec) at temperature T_s (K) through 100% of oxygen gas and the ultrasonic propagation velocity C_{N_2} (m/sec) at
25 temperature T_s (K) through 100% of nitrogen gas can be easily obtained by using equation (1). Thus, P_s can be calculated by following equation (7) with the ultrasonic propagation velocity C_s (m/sec) through the sample gas.

$$P_s = (1/C_s^2 - 1/C_{N_2}^2) / (1/C_{O_2}^2 - 1/C_{N_2}^2) \dots (7)$$

30 Such calculations are conducted by the microcomputer 126, and the results are indicated by the display unit 134.

35 Next, the explanation will be directed to a method of obtaining t_{s1} and t_{s2} . In this connection, the moment when the first or second ultrasonic transducer 218 or 222 transmits the ultrasonic waves is referred to as an

emission time and the moment when the first or second ultrasonic transducer 218 or 222 receives the ultrasonic waves is referred to as an ultrasonic reception point in the present application.

5 Figure 3A shows a typical ultrasonic waveform received by the microcomputer 226 and Figure 3B is an enlargement of a portion of the waveform shown by circle 3B. As shown by Figures 3A and 3B, the waveform includes a various noise components which make difficult to detect
10 the ultrasonic reception point of the ultrasonic waves propagating through the sample gas. Therefore, according to the present invention, the ultrasonic reception point is estimated on basis of the zero-cross time instant of the waveform which is detected after the amplitude of the
15 waveform sufficiently increases to an extent. For this purpose, the zero-cross detection circuit 230 includes a zero-cross comparator and a trigger comparator.

 Referring to Figure 4, the trigger comparator outputs a trigger signals S_{ti} to the microcomputer 226
20 when the waveform upwardly passes over a predetermined level. The zero-cross comparator outputs a zero-cross signal Z_{ci} to the microcomputer 226 when the waveform upwardly passes over the zero level. The microcomputer 226 determines each of the zero-cross signals Z_{ci} as a
25 zero-cross time instant after the first trigger signal S_{t1} is received by the microcomputer 226. Preferably, the microcomputer 226 determines first three zero-cross signals as first to third zero-cross time instants Z_{c1} , Z_{c2} and Z_{c3} .

30 The interval between each of the zero-cross time instants theoretically corresponds to the cycle of the ultrasonic waves. Therefore, the ultrasonic reception point can be estimated by tracing back from the first zero-cross time instant Z_{c1} along the time axis by an
35 integral multiple of the cycle of the ultrasonic waves and therefore, the propagation time can be estimated by subtracting the emission time and an integral multiple of

the cycle of the ultrasonic waves from the ultrasonic reception point.

As described above, the velocity of ultrasonic waves C (m/sec) propagating through a stationary gas is presented by equation (1). For example, the velocity of ultrasonic waves through a pure nitrogen gas at 20 Celsius degrees is 349.1 m/sec, and the velocity of ultrasonic waves through a pure oxygen gas at 20 Celsius degrees is 326.6 m/sec. Therefore, at 20 Celsius degrees, the velocity of ultrasonic waves through an oxygen-nitrogen gas mixture falls within the range of 326.6 to 49.1 m/sec. Figure 5 is a graph showing the relation between the velocity of ultrasonic waves and the gas temperature, in which the upper and lower limits of the ultrasonic velocity through an oxygen-nitrogen gas mixture are indicated by $C_{\max}(T)$ and $C_{\min}(T)$. The possible propagation time range is $L_s/C_{\max}(T)$ to $L_s/C_{\min}(T)$. Therefore, if the propagation length L_s is selected to satisfy following relation (8), only one integer can be selected which allows the ultrasonic reception point to fall within the possible propagation time range.

$$(L_s/C_{\min}(T) - L_s/C_{\max}(T)) < 1/f \dots(8)$$

where:

f : frequency of the ultrasonic waves in the sample gas
The gas temperature T which gives the maximum value of $(L_s/C_{\max}(T) - L_s/C_{\min}(T))$ is the lower limit of the working temperature. If the working temperature is 5 Celsius degrees, and the frequency of the ultrasonic waves is 40 KHz, the propagation length L_s which satisfies relation (8) is calculated as follows.

$$L_s < 12.3 \text{ cm} \dots(9)$$

According to the embodiment, $L_s=0.1$ m is employed as an example.

In order to obtain the ultrasonic propagation time t_s , the forward and backward propagation times t_{s1} and t_{s2} is previously measured. With reference to Figure 6, the

trigger signals are generated when the second waves in both the forward and backward waveforms passes over the trigger level. In this case, the trigger signals are generated at the same timing or phase relative to the waveforms and the difference in the zero-cross time instants between the forward and backward waves, $A = Z_{cBi} - Z_{cFi}$, is substantially equal to the difference t_d in propagation times t_{s1} and t_{s2} between the forward and backward waves (Z_{cFi} : the zero-cross time instants of the forward waveform, Z_{cBi} : the zero-cross time instants of the backward waveform, $i=1, 2, 3...$ (wave number)).

However, the trigger signals S_{ti} are often generated at different phases of the waveforms between the forward and backward waves, even if the same trigger level is used. Referring to Figure 7, for the forward waves, the trigger signal is generated when the third wave passes over the trigger level and for the backward waves, the trigger signal is generated when the second wave passes over the trigger level. Therefore, the trigger signal for the backward waves is generated at one cycle earlier than the trigger signal for the forward waves. In this case, the difference in the zero-cross time instants between the forward and backward waves, $A = Z_{cBi} - Z_{cFi}$, gives a negative value. If the sample gas flows through the conduit 102, $A = Z_{cBi} - Z_{cFi}$ must not become negative. Therefore, if $A = Z_{cBi} - Z_{cFi}$ gives a negative value, it is apparent that the trigger signal for the backward waves is generated earlier than the trigger signal for the forward waves.

On the other hand, referring to Figure 8, for the forward waves, the trigger signal is generated when the second wave passes over the trigger level and for the backward waves, the trigger signal is generated when the third wave passes over the trigger level. In this case, the difference in the zero-cross time instants between the forward and backward waves, $A = Z_{cBi} - Z_{cFi}$, exceeds one cycle of the ultrasonic waves, which indicates that

the trigger signal for the forward waves is generated earlier than the trigger signal for the backward waves.

According to the embodiment of the invention, the conduit 102 is designed so that the propagation time difference t_d between the forward and backward waves always falls within one cycle of the ultrasonic waves. This feature allows the microcomputer 226 to distinguish the cases shown in Figures 7 and 8 from each other and to calculate the propagation time difference t_d . That is, if $A = Z_{cBi} - Z_{cFi}$ is negative, the case is as shown in Figure 7 and if $A = Z_{cBi} - Z_{cFi}$ exceeds one cycle of the ultrasonic waves the case is as shown in Figure 8.

Thus, the configuration of conduit 102 which has the above feature will be described below.

The possible range of the flow velocity V (m/sec) of the sample gas is presented by following inequality (10).

$$0 \leq V \leq Q / (60000\pi / r^2) \quad \dots (10)$$

where:

Q : flow rate of the sample gas (litter/min)

r : inner radius of the conduit (cm)

As described above, the velocity of ultrasonic waves propagated in the forward direction relative to the sample gas flow is $C_1 = C + V$, and the velocity of ultrasonic waves propagated in the backward direction relative to the sample gas flow is $C_2 = C - V$.

Where:

C : the velocity of ultrasonic waves propagating through a stationary sample gas (m/sec)

C_1 : the velocity of the ultrasonic waves propagated in the forward direction relative to the sample gas flow (m/sec)

C_2 : the velocity of ultrasonic waves propagated in the backward direction relative to the sample gas flow (m/sec)

V : the flow velocity (m/sec)

The propagation time difference t_d is calculated by the following equation.

$$\begin{aligned} t_d &= L_s/C_2 - L_s/C_1 \\ &= L_s/(C-V) - L_s/(C+V) \dots(11) \end{aligned}$$

Therefore, if the inner radius of the conduit 102 satisfies following relation (12), the propagation time difference t_d becomes smaller than the cycle of the ultrasonic waves.

$$L_s / (C - Q / (60000\pi / r^2)) - L_s / (C + Q / (60000\pi / r^2)) < 1/f \dots(12)$$

The left term of inequality (12) is maximized when the velocity of the ultrasonic waves through the conduit 102 is minimum ($C = C_{\min}(5 \text{ Celsius degrees}) = 318.1 \text{ m/sec}$). Therefore, for example, if the frequency of the ultrasonic waves through the conduit 102 is 40 (KHz), the flow rate $Q = 10$ (litter/min) and the length of the conduit 102 is 10 (cm), then the inner radius r (mm) of the conduit 102 is $r > 2.05$ (mm). According to the embodiment, $r = 2.5$ (mm) is selected as an example.

Next, the method for measuring the concentration and flow rate of a sample gas will be described in detail below.

First, in case shown in Figure 6, the propagation time difference t_d between the forward and backward waves is obtained by $A = Z_{cBi} - Z_{cFi}$, because, as described above, the propagation time difference t_d is substantially equal to the difference $A = Z_{cBi} - Z_{cFi}$. In case shown in Figure 7, the propagation time difference t_d is obtained by $B = Z_{cBi+1} - Z_{cFi}$. Further, in case shown in Figure 8, the propagation time difference t_d is obtained by $B = Z_{cBi} - Z_{cFi+1}$. Preferably, a plurality of the values A or B are obtained for arithmetic average.

Next, the velocity of the ultrasonic waves through the sample gas is estimated with the assumption that the sample gas is in stationary state. For this purpose, the phase difference in the outputs of the trigger signals is previously determined on the basis of the value of A . If there is no phase difference, as shown in Figure 6, mean value Z_{c_ave} of first zero-cross time instants of the

forward and backward waveforms is calculated by the following equation.

$$Z_{c_ave} = (Z_{cF1} + Z_{cB1}) / 2 \dots (13)$$

In case shown in Figure 7, mean value Z_{c_ave} of first zero-cross time instants of the forward and backward waveforms is calculated by the following equation.

$$Z_{c_ave} = (Z_{cF1} + Z_{cB2}) / 2 \dots (14)$$

In case shown in Figure 8, mean value Z_{c_ave} of first zero-cross time instants of the forward and backward waveforms is calculated by the following equation.

$$Z_{c_ave} = (Z_{cF2} + Z_{cB1}) / 2 \dots (15)$$

The mean value Z_{c_ave} can be considered as the first zero-cross time instant which is obtained with the assumption of the ultrasonic waves through the stationary sample gas. Z_{c_ave} is referred to a reference zero-cross time instant in the present application.

As described above, the length of the conduit 102 is designed so that only one integer is selected allowing the ultrasonic reception point to fall in the possible range of the propagation time (Figure 9). Therefore, the ultrasonic propagation time t_s is estimated by tracing back from the first zero-cross time instant Z_{c_ave} along the time axis by an integral multiple of the cycle of the ultrasonic waves until the ultrasonic reception point falls in the possible range.

The velocity of the ultrasonic waves C_s through the stationary sample gas is estimated by following equation (16).

$$C_s = L_s / t_s \dots (16)$$

The concentration of oxygen P_s is obtained by equation (6) or (7) with the calculated C_s .

The forward and backward propagation times t_{s1} and t_{s2} through the sample gas flowing through the conduit 102 are estimated by following equations (17) and (18).

$$t_{s1} = t_s - t_d / 2 \dots (17)$$

$$t_{s1}=t_s+t_d/2 \dots(18)$$

The forward and backward velocities C_1 and C_2 of the ultrasonic waves through the sample gas flowing through the conduit 102 are estimated by following equations (19) and (20).

$$C_1=L_s/t_{s1} \dots(19)$$

$$C_2=L_s/t_{s2} \dots(20)$$

Then, the flow velocity V of the sample gas through the conduit 102 is obtained by equations (3), (19) and (20). Further, the flow rate Q of the sample gas is calculated by following equation (21).

$$Q=6000\pi r^2V \dots(21).$$

Next, with reference to Figures 11 to 15, a preferred embodiment of the ultrasonic concentration and flow rate measurement apparatus will be described below.

the ultrasonic concentration and flow rate measurement apparatus 10 includes a conduit 27 which provides the conduit 102 of the embodiment of Figure 2. Housings 25 and 26, for enclosing first and second ultrasonic transducers 20 and 21, secured to the ends of the conduit 27 by welded portions 41 and 42. The housings 25 and 26 include ports 28 and 29 extending perpendicular to the conduit 27 to provide the inlet and outlet portions 204a and 206a of the embodiment of Figure 2. The conduit 27 and the housings 25 and 26 are preferably made of the same metallic material such as an aluminum alloy.

The conduit 27 and the housings 25 and 26 are secured at one point to a substrate 30 or a housing of the oxygen concentration apparatus by a screw 45. This configuration allows the longitudinal deformation of the conduit 27 freely from external force which may be generated when the conduit 27 is thermally deformed.

Covers 23 and 24 are attached to the housings 25 and 26 to close the end openings of the housings by screws 43 and 44 with O-rings 39 and 40 being clamped between the

housings 25 and 26 and the covers 23 and 24. The first
 and second ultrasonic transducers 20 and 21 are attached
 to the inner surfaces of the covers 23 and 24. The first
 and second ultrasonic transducers 20 and 21 generate 40
 5 KHz of ultrasonic waves.

Further, temperature sensors 37 and 38 for detecting
 the gas temperature are attached to the inner surfaces of
 the covers 23 and 24. The first and second ultrasonic
 transducers 20 and 21 and the temperature sensors 37 and
 10 38 are coupled to the microcomputer 226 through
 connectors 31 and 34 attached to the outer surfaces of
 the covers 23 and 24, cables 33 and 36 and connectors 32
 and 35 mounted on the substrate 30.

Distance D between the end faces of the first and
 15 second ultrasonic transducers 20 and 21 and the
 respective ends of the conduit 27 is a significant design
 matter. Generally, the sound field formed by the
 ultrasonic waves from an ultrasonic transducer includes
 near and far sound fields, as shown in Figure 12. The
 20 ultrasonic waves propagate linearly through the near
 sound field and on the other hand, in the far sound
 field, spread in the form of spherical waves. Therefore,
 if the ends of the conduit 27 are out of the near sound
 field, the ultrasonic energy transmitted in the conduit
 25 27 is reduced compared with conduit having the ends
 disposed in the near sound field and therefore, the
 sound/noise ratio of the signal from the transducers is
 reduced.

It is known that the boundary between the near and
 30 far sound fields is presented at a point Z_0 the distance
 D of which from the end face of an ultrasonic transducer
 along the center line of the transducer is defined by
 following equation (22).

$$D=f-r^2/C \dots(22)$$

35 Where:

f: frequency of the ultrasonic waves in the sample gas
 (Hz)

r: inner radius of the conduit (m)

C: velocity of the ultrasonic waves (m/sec)

As described above, the velocity C through a sample gas is defined by equation (1). Therefore, the higher the gas temperature and the smaller the molecular weight, the higher the velocity C becomes. According to the embodiment, the condition which maximizes Z_0 is that, for example, the sample gas is the air at 35 Celsius degrees and then, Z_0 is about 1.4 mm.

Figures 13-15 show experimental results of ultrasonic waveforms which were obtained by an apparatus of Figure 11 with the distance d of 0.3 mm, 1.0 mm and 1.8 mm. The experimental results suggest that the ultrasonic energy received by the ultrasonic transducer is significantly reduced when the distance d is 1.8 mm compared with the cases of the distance d of 0.3 mm and 1.0 mm.

CLAIMS

1. An ultrasonic apparatus for measuring the concentration and flow rate of a sample gas, comprising:
 - a conduit for flowing the sample gas;
 - 5 a first ultrasonic transmission-reception device mounted to the inside of the conduit;
 - a second ultrasonic transmission-reception device mounted to the inside of the conduit to face the first ultrasonic transmission-reception device;
 - 10 a transmission-reception switch for switching the operation mode of the first and second ultrasonic transmission-reception devices between a transmission mode for transmitting ultrasonic waves and a reception mode for receiving ultrasonic waves;
 - 15 a temperature sensor, disposed in the conduit, for measuring the temperature of the sample gas flowing through the conduit;
 - the first ultrasonic transmission-reception device generating forward ultrasonic waves relative to the flow direction of the sample gas when the device is in the transmission mode and generating backward waveform when the device is in the reception mode on the basis of the received ultrasonic waves generated by the second ultrasonic transmission-reception device;
 - 25 the second ultrasonic transmission-reception device generating backward ultrasonic waves relative to the flow direction of the sample gas when the device is in the transmission mode and generating forward waveform when the device is in the reception mode on the basis of the received ultrasonic waves generated by the first ultrasonic transmission-reception device;
 - means for generating trigger signals when the forward and backward waveforms pass over a predetermined level;
 - 35 means for generating forward and backward zero-cross signals when the forward and backward

waveforms pass over a zero level;

propagation time calculation means,
coupled to the temperature sensor, the trigger signal
generating means and the zero-cross signal generating
5 means, for (1) calculating a possible propagation time
range on the basis of the gas temperature detected by the
temperature sensor, (2) determining whether or not the
phases at which two first trigger signals, respectively
generated on the basis of the forward and backward
10 waveforms, coincide with each other, (3) processing the
zero-cross signals so that the phases coincide with each
other if they do not coincide with each other, (4)
obtaining reference zero-cross time instant by
calculating mean value of the forward and backward zero-
15 cross time instants, (5) obtaining an ultrasonic
reception point by subtracting an integral multiple of
the cycle of the ultrasonic waves so that the results of
the subtraction falls into the possible propagation time
range and (6) estimating the ultrasonic propagation time
20 on the basis of the ultrasonic reception point.

2. An ultrasonic apparatus according to claim 1
wherein the distance along the conduit between first and
second ultrasonic transmission-reception devices is
selected so that only one result of the subtraction falls
25 into the possible propagation time range determined over
possible working conditions of the ultrasonic apparatus.

3. An ultrasonic apparatus according to claim 2
wherein the distance along the conduit between first and
second ultrasonic transmission-reception devices is
30 sleeted to satisfy the following relation.

$$(L_s/C_{\min}(T_{\min}) - L_s/C_{\max}(T_{\min})) < 1/f$$

where:

f: frequency of the ultrasonic waves in the sample
gas

35 $C_{\min}(T_{\min})$: the lower limit of the ultrasonic velocity
(m/sec) through the sample gas at the lowest working
temperature T_{\min} (Celsius degrees)

$C_{\max}(T_{\min})$: the upper limit of the ultrasonic velocity (m/sec) through the sample gas at the lowest working temperature T_{\min} (Celsius degrees)

4. An ultrasonic apparatus according to claim 1
5 wherein the inner radius of the conduit is selected so that the difference between the forward and backward propagation time is smaller than the cycle of the ultrasonic waves under the working condition of the sample gas.

10 5. An ultrasonic apparatus according to claim 1 wherein the inner radius of the conduit is selected to satisfy the following relation

$$\begin{aligned} &L/(C_{\min}(T_{\min})-Q_{\max}/(60000\pi/r^2)) \\ &-L/(C_{\min}(T_{\min})+Q_{\max}/(60000\pi/r^2)) < 1/f \end{aligned}$$

15 where:

f : frequency of the ultrasonic waves in the sample gas

$C_{\min}(T_{\min})$: the lower limit of the ultrasonic velocity (m/sec) through the sample gas at the lowest working
20 temperature T_{\min} (Celsius degrees)

Q_{\max} : the upper limit of the sample gas flow rate (litter/min)

6. An ultrasonic apparatus according to claim 1
25 wherein the conduit includes a straight portion and perpendicular portions perpendicularly connected to the ends of the straight portion;

the first and second ultrasonic transmission-reception devices are disposed in the perpendicular portions to face the ends of the straight
30 portion; and

the distance between the first and second ultrasonic transmission-reception devices and the respective ends of the straight portion of the conduit satisfying the following relation.

35 $0 < D < f - r^2/C$

D : the distance (m) between the first and second

ultrasonic transmission-reception devices and the respective ends of the straight portion

f: frequency of the ultrasonic waves in the sample gas (Hz)

5 r: inner radius of the conduit (m)

C: velocity of the ultrasonic waves (m/sec)

7. A method of measuring the concentration of sample gas flowing through a conduit, comprising the steps of:

10 generating forward ultrasonic waves relative to the flow direction of the sample gas;
generating backward ultrasonic waves relative to the flow direction of the sample gas;
measuring the temperature of the sample
15 gas flowing through the conduit;
generating trigger signals when the forward and backward waveforms pass over a predetermined level;
generating forward and backward zero-cross
20 signals when the forward and backward waveforms pass over a zero level;
calculating a possible propagation time range on the basis of the gas temperature detected by the temperature sensor;
25 determining whether or not the phases at which two first trigger signals, respectively generated on the basis of the forward and backward waveforms, coincide with each other;
processing the zero-cross signals so that
30 the phases coincide with each other if they do not coincide with each other;
obtaining reference zero-cross time instant by calculating mean value of the forward and backward zero-cross time instants;
35 obtaining an ultrasonic reception point by subtracting an integral multiple of the cycle of the ultrasonic waves so that the results of the subtraction

falls into the possible propagation time range; and
estimating the ultrasonic propagation time
on the basis of the ultrasonic reception point.

8. A method according to claim 7 wherein the
5 forward and backward ultrasonic waves are transmitted and
received by first and second ultrasonic transmission-
reception devices which are disposed in the conduit, the
distance along the conduit between first and second
ultrasonic transmission-reception devices being selected
10 so that only one result of the subtraction falls into the
possible propagation time range determined over possible
working conditions of the ultrasonic apparatus.

9. A method according to claim 8 wherein the
distance along the conduit between first and second
15 ultrasonic transmission-reception devices is selected to
satisfy the following relation.

$$(L_s/C_{\min}(T_{\min}) - L_s/C_{\max}(T_{\min})) < 1/f$$

where:

20 f: frequency of the ultrasonic waves in the sample
gas

$C_{\min}(T_{\min})$: the lower limit of the ultrasonic velocity
(m/sec) through the sample gas at the lowest working
temperature T_{\min} (Celsius degrees)

25 $C_{\max}(T_{\min})$: the upper limit of the ultrasonic velocity
(m/sec) through the sample gas at the lowest working
temperature T_{\min} (Celsius degrees)

10. A method according to claim 7 wherein the inner
radius of the conduit is selected so that the difference
between the forward and backward propagation time is
30 smaller than the cycle of the ultrasonic waves under the
working condition of the sample gas.

11. A method according to claim 7 wherein the inner
radius of the conduit is selected to satisfy the
following relation

35
$$L/(C_{\min}(T_{\min}) - Q_{\max}/(60000\pi/r^2))$$
$$- L/(C_{\min}(T_{\min}) + Q_{\max}/(60000\pi/r^2)) < 1/f$$

where:

f : frequency of the ultrasonic waves in the sample gas

5 $C_{\min}(T_{\min})$: the lower limit of the ultrasonic velocity (m/sec) through the sample gas at the lowest working temperature T_{\min} (Celsius degrees)

Q_{\max} : the upper limit of the sample gas flow rate (litter/min)

10 12. An oxygen concentration system for generating an oxygen enriched gas, comprising

an oxygen concentration apparatus for generating an oxygen enriched gas by adsorbing nitrogen to remove the nitrogen from the air; and

15 an ultrasonic apparatus for measuring the concentration of the oxygen in the oxygen enriched gas and flow rate of the oxygen enriched gas, the ultrasonic apparatus comprising:

a conduit for receiving and flowing the oxygen enriched gas;

20 a first ultrasonic transmission-reception device mounted to the inside of the conduit;

a second ultrasonic transmission-reception device mounted to the inside of the conduit to face the first ultrasonic transmission-reception device;

25 a transmission-reception switch for switching the operation mode of the first and second ultrasonic transmission-reception devices between a transmission mode for transmitting ultrasonic waves and a reception mode for receiving ultrasonic waves;

30 a temperature sensor, disposed in the conduit, for measuring the temperature of the oxygen enriched gas flowing through the conduit;

35 the first ultrasonic transmission-reception device generating forward ultrasonic waves relative to the flow direction of the oxygen enriched gas when the device is in the transmission mode and generating backward waveform when the device is in the

reception mode on the basis of the received ultrasonic waves generated by the second ultrasonic transmission-reception device;

5 the second ultrasonic transmission-reception device generating backward ultrasonic waves relative to the flow direction of the oxygen enriched gas when the device is in the transmission mode and generating forward waveform when the device is in the reception mode on the basis of the received ultrasonic
10 waves generated by the first ultrasonic transmission-reception device;

 means for generating trigger signals when the forward and backward waveforms pass over a predetermined level;

15 means for generating forward and backward zero-cross signals when the forward and backward waveforms pass over a zero level;

 propagation time calculation means, coupled to the temperature sensor, the trigger signal generating means and the zero-cross signal generating means, for (1) calculating a possible propagation time range on the basis of the gas temperature detected by the temperature sensor, (2) determining whether or not the phases at which two first trigger signals, respectively
20 generated on the basis of the forward and backward waveforms, coincide with each other, (3) processing the zero-cross signals so that the phases coincide with each other if they do not coincide with each other, (4) obtaining reference zero-cross time instant by
25 calculating mean value of the forward and backward zero-cross time instants, (5) obtaining an ultrasonic reception point by subtracting an integral multiple of the cycle of the ultrasonic waves so that the results of the subtraction falls into the possible propagation time range and (6) estimating the ultrasonic propagation time
30 on the basis of the ultrasonic reception point.
35

13. An ultrasonic apparatus according to claim 12

wherein the distance along the conduit between first and second ultrasonic transmission-reception devices is selected so that only one result of the subtraction falls into the possible propagation time range determined over possible working conditions of the ultrasonic apparatus.

14. An ultrasonic apparatus according to claim 13 wherein the distance along the conduit between first and second ultrasonic transmission-reception devices is selected to satisfy the following relation.

$$(L_s/C_{\min}(T_{\min}) - L_s/C_{\max}(T_{\min})) < 1/f$$

where:

f: frequency of the ultrasonic waves in the sample gas

$C_{\min}(T_{\min})$: the lower limit of the ultrasonic velocity (m/sec) through the oxygen enriched gas at the lowest working temperature T_{\min} (Celsius degrees)

$C_{\max}(T_{\min})$: the upper limit of the ultrasonic velocity (m/sec) through the oxygen enriched gas at the lowest working temperature T_{\min} (Celsius degrees)

15. An ultrasonic apparatus according to claim 12 wherein the inner radius of the conduit is selected so that the difference between the forward and backward propagation time is smaller than the cycle of the ultrasonic waves under the working condition of the oxygen enriched gas.

16. An ultrasonic apparatus according to claim 12 wherein the inner radius of the conduit is selected to satisfy the following relation

$$\begin{aligned} & L/(C_{\min}(T_{\min}) - Q_{\max}/(60000\pi/r^2)) \\ & - L/(C_{\min}(T_{\min}) + Q_{\max}/(60000\pi/r^2)) < 1/f \end{aligned}$$

where:

f: frequency of the ultrasonic waves in the sample gas

$C_{\min}(T_{\min})$: the lower limit of the ultrasonic velocity (m/sec) through the oxygen enriched gas at the lowest working temperature T_{\min} (Celsius degrees)

Q_{\max} : the upper limit of the oxygen enriched gas flow rate (litter/min)

17. An ultrasonic apparatus according to claim 12 wherein the conduit includes a straight portion and perpendicular portions perpendicularly connected to the ends of the straight portion;

the first and second ultrasonic transmission-reception devices are disposed in the perpendicular portions to face the ends of the straight portion; and

the distance between the first and second ultrasonic transmission-reception devices and the respective ends of the straight portion of the conduit satisfying the following relation.

$$0 < D < f - r^2 / C$$

D: the distance (m) between the first and second ultrasonic transmission-reception devices and the respective ends of the straight portion

f: frequency of the ultrasonic waves in the sample gas (Hz)

r: inner radius of the conduit (m)

C: velocity of the ultrasonic waves (m/sec)

18. An ultrasonic apparatus according to claim 12 wherein the conduit is secured to the oxygen concentration apparatus at one point to allow the conduit to thermally expand in the longitudinal direction of the straight portion freely from external force which may be generated when the conduit is thermally deformed.

19. An oxygen concentration system for generating an oxygen enriched gas, comprising:

an oxygen concentration apparatus for generating an oxygen enriched gas by adsorbing nitrogen to remove the nitrogen from the air; and

an ultrasonic apparatus for measuring the concentration of the oxygen in the oxygen enriched gas and flow rate of the oxygen enriched gas, the ultrasonic apparatus comprising:

a conduit for flowing an objective gas,
the concentration of which is to be measured;

a first ultrasonic transmission-reception
device mounted to the inside of the conduit;

5 a second ultrasonic transmission-reception
device mounted to the inside of the conduit to face the
first ultrasonic transmission-reception device;

the conduit includes a straight portion and
perpendicular portions perpendicularly connected to the
10 ends of the straight portion;

the first and second ultrasonic
transmission-reception devices are disposed in the
perpendicular portions to face the ends of the straight
portion; and

15 the distance between the first and second
ultrasonic transmission-reception devices and the
respective ends of the straight portion of the conduit
satisfying the following relation.

$$0 < D < f - r^2 / C$$

20 where:

D: the distance (m) between the first and second
ultrasonic transmission-reception devices and the
respective ends of the straight portion

f: frequency of the ultrasonic waves in the sample
25 gas (Hz)

r: inner radius of the conduit (m)

C: velocity of the ultrasonic waves (m/sec)

20. An oxygen concentration system according to
claim 19 wherein the inner diameter of the straight
30 portion is smaller than the outer diameter of first and
second ultrasonic transducers.

21. An oxygen concentration system according to
claim 19 wherein the conduit is secured to the oxygen
concentration apparatus by means for allowing the
35 longitudinal deformation of the straight portion freely
from external force which may be generated when the
conduit is thermally deformed.

22. An oxygen concentration system according to
claim 19 wherein the conduit is secured to the oxygen
concentration apparatus at one point to allow the conduit
to thermally expand in the longitudinal direction of the
5 straight portion freely from external force which may be
generated when the conduit is thermally deformed.

ABSTRACT

5 An ultrasonic apparatus measures the concentration
and flow rate of a sample gas by calculating a possible
propagation time range on the basis of the gas
temperature, determining whether or not the phases at
which two first trigger signals, respectively generated
on the basis of forward and backward waveforms of the
ultrasonic waves, coincide with each other, processing
10 the zero-cross signals so that the phases coincide with
each other, obtaining reference zero-cross time instant
by calculating mean value of the forward and backward
zero-cross time instants, obtaining an ultrasonic
reception point by subtracting an integral multiple of
15 the cycle of the ultrasonic waves so that the results of
the subtraction falls into a possible propagation time
range and estimating the ultrasonic propagation time on
the basis of the ultrasonic reception point.